




12030 CASALGRASSO-CN- ITALY
 funiflex.sollevamenti@gmail.com


FUNIFLEX SOLLEVAMENTI SRL

TIRANT CAPOCORDA FILETTATI/OCHIO/FORCELLA



safety factor de la 3 la 5:1

EN 13411



Ø FUNE mm	RESISTENZA				ACCESORII CAPOCORDA APERTO/CHIUSO SWAGED SOCKED						ACCESORII FILETTATI SWAGED THREADED			
	r.1770	r.1960	r.2160	spiroid.	A	C	D	B	E	F	G	H	M	N
	kN	kN	kN	kN	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
6	21.69	26.46	31.23	-	-	-	-	-	-	-	119	11.8	50	M12x1.75
8	38.52	46.98	55.44	-	21	44	21	22.2	17.5	43	151	15.2	65	M16x2
10	67.86	75.96	86.67	-	21	44	21	22.2	17.5	43	184	18.3	80	M20x2.5
11	-	91.8	105.3	98.1	21	44	25	22.2	17.5	43	184	18.3	80	M20x2.5
12	90.45	109.8	125.1	116.1	25	51	25	27	22.2	51	222	23.4	100	M24x3
13	-	-	-	136.8	25	51	25	27	22.2	51	230	23.4	100	M24x3
14	134.1	148.5	171.9	-	32	57	30	31.8	28.6	63	263	30	120	M30x3.5
15	-	-	-	181.8	32	57	30	31.8	28.6	63	272	30	120	M30x3.5
16	175.5	194.4	224.1	-	32	57	30	31.8	28.6	63	281	30	120	M30x3.5
18	218.52	245.7	284.4	-	38	70	35	37.3	33.3	76	328	36.8	150	M36x4
19	-	274.5	316.8	289.8	38	70	35	37.3	33.3	76	337	36.8	150	M36x4
20	275.4	304.2	351	321.3	38	70	35	37.3	33.3	76	346	36.8	150	M36x4
22	333	367.2	423.9	387	44	83	41	43.7	38.1	89	394	40	170	M42x4.5
24	396.54	437.4	504.9	460.8	51	95	51	52	44	102	441	46.7	200	M48x5
26	424.8	513.9	588.6	540.9	51	95	51	52	44	102	459	46.7	200	M48x5
28	492.3	595.8	683.1	627.3	57	108	57	59	51	114	476	53.4	200	M48x5
30	565.2	684	783.9	-	63	121	64	65	57	127	514	53.4	220	M56x5.5
32	643.5	777.6	891.9	818.1	63	121	64	65	57	127	542	60	220	M56x5.5
34	726.3	858.6	1008	-	63	133	64	65	57	133	559	60	220	M64x5.5
36	813.6	963	1125	1035	63	133	64	65	57	133	597	66.7	240	M64x5.5
38	906.3	1071	1260	-	76	146	70	71	63	140	644	66.7	270	M64x5.5
40	1008	1188	1395	1278	76	146	70	72	63.5	140	672	72.5	270	M64x5.5