

[funiflex.sollevamenti@gmail.com](mailto:funiflex.sollevamenti@gmail.com)  
12030Casalgrasso-CN-Italy

[info.funiflexsollevamenti@gmail.com](mailto:info.funiflexsollevamenti@gmail.com)  
[sales.funiflexsollevamenti@gmail.com](mailto:sales.funiflexsollevamenti@gmail.com)

**GROMMET STEEL WIRE ROPE SLING WITH STEEL CORE EN 13414-3**  
**BRACHE AD ANELLO CONTINUO IN FUNE ACCIAIO R.2160**

PESO / MT		Metallica	PESO kg	ASOLE	Coef.sic.
	DIAM.	WLL : IWRC	MT/sviluppo	SOFT EYE	Safety F.
1,9 KG	24	10,7 T	1,9KG	290X145 MM	5
2,4 KG	27	13,5 T	2,4KG	320X160 MM	5
3 KG	30	18,7 T	3 KG	360X180 MM	5
3,7 KG	33	22,5 T	3,7KG	360X180 MM	5
4,4 KG	36	26,5 T	4,4KG	430X215 MM	5
5,1 KG	39	31 T	5,1KG	470X235 MM	5
6 KG	42	36 T	6KG	500X250 MM	5
6,8 KG	45	41,5 T	6,8KG	500X250 MM	5
7,8 KG	48	47 T	7,8KG	580X290 MM	5
9,8 KG	54	59,9 T	9,8KG	650X325 MM	5
11 KG	57	66 T	11KG	720X360 MM	5
12 KG	60	74,2 T	12KG	720X360 MM	5
14,8 KG	66	91,8 T	14,8KG	800X400 MM	4,88
17,6 KG	72	100,7 T	17,6KG	860X430MM	4,75
20,5 KG	78	121,7 T	20,5KG	940X470MM	4,61
24 KG	84	152,4 T	24KG	1000X500MM	4,48
27,5 KG	90	171,5 T	27,5 KG	1200X600MM	4,35
31 KG	96	201 T	31 KG	1200X600MM	4,22
35,5 KG	102	217,3 T	* 35 KG	1300X650MM	4,09
40 KG	108	252,3 T	* 39 KG	1300X350MM	3,95
44,5 KG	114	290,6 T	* 44 KG	1400X700MM	3,82
49 KG	120	333,37 T	* 50 KG	1400X700MM	3,69

2025

